



iSuna | 10+ years in storage inverter

Sinexcel

Stock Code:300693



RESIDENTIAL Storage Inverter



Solar+Storage Hybrid Inverter



Single Phase: 3kW-10kW



Three Phase: 5kW-20kW



Wide Range of Power



Strong Battery Voltage Compatibility



VPP Interface Ready

01 Single / Three Phase Hybrid Inverter Load Controller

Higher Reliability

IP65 Outdoor&Indoor use
 Natural cooling, Ultra silence
 SiC technology, Longer lifespan
 Plug-in design, Easy to install

High Capability

15 units in parallel
 2 independent ports for battery
 Support mixture use of old & new battery

Auto sleep
 VPP interface ready
 Cloud + Smart data analysis

Smart Monitoring

UPS function
 Flexible DO control
 10ms on/off-grid switchover
 100% three phase unbalance

Strong Load Adaptability

02 Typical Configuration



03 Single Phase Datasheet

Model Name	Isuna 3000S	Isuna 3600S	Isuna 4000S	Isuna 4600S	Isuna 5000S	Isuna 6000S
Off-grid Output						
Nominal Output Power	3000W	3600W	4000W	4600W	5000W	6000W
Nominal Voltage	220V/230V/240V					
Nominal Frequency	50/60Hz					
Nominal Output Current	13.6A	16.4A	18.2A	20.8A	22.7A	27.2A
Output THDu	<2%					
On-grid Parameter						
Nominal Output Power	3000W	3600W	4000W	4600W	5000W	6000W
Max. Output Current	13.6A	16.4A	18.2A	20.8A	22.7A	27.2A
Nominal Grid Voltage	220V/230V/240V					
Max. Input Current from Grid	16.4A	22.7A		27.2A		
Grid Voltage Range	184-276V					
Frequency Range	45-65Hz					
PV Input						
Max. Input Power	4500Wp	6000Wp		7500Wp		9000Wp
Starting Voltage	95V					
Max. Input Voltage	600V					
MPPT Voltage Range	80-550V					
Full Load MPPT Voltage Range	350-500V					
Number of MPPT	2					
Max. Input String Per MPPT	1					
Nominal Input Voltage	360V					
Max. Input Current	13A/13A					
Battery Parameter						
Battery Type	Lithium-ion					
Nominal Battery Voltage	51.2V					
Battery Voltage Range	42-58V					
Max. Charging Voltage	≤60V					
Max. Continuous Discharging Current	75A	85A		100A		
Efficiency						
Max. Efficiency	97.5%		97.8%		98.0%	
European Efficiency	97.2%		97.3%		97.5%	
Max. Battery Charging/Discharging Efficiency	95.2%					
General Data						
Size(W*H*D)	515mm*490mm*184mm					
Weight	23kg					
Noise	<25dB(A)					
Operating Temperature Range	-25°C~+60°C					
Cooling Method	Natural cooling					
Ingress Protection Grade	IP65					
Monitoring	LED/APP/WIFI/4G/Bluetooth					
Communication Port	RS485/CAN/DRED/DO/Parallel port					
Protection	DC Switch, PV Insulation Resistance Detection, Residual Current Monitoring, Anti-islanding Protection, Reverse Polarity Protection(PV&Battery) AC Short Circuit Protection, AC Overcurrent Protection, AC Overvoltage Protection:LEVEL III;PV&Battery:LEVEL II, Surge Protection, Lightning Protection:TYPE II					
Certification						
CE_LVD	IEC 62109-1, IEC 62109-2, EN 62109-1, EN 62109-2					
CE EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4					
Grid	VDE-AR-N 4105, VDE V 0126-1-1, C10-11,G99, CEI 0-21, EN50549, NRS 097-2-1, AS 4777.2, R25,UNE217001,UNE217002,NTS 2.1					